



# FLOOD LIGHT(FD03)

## Applications:

Facade, Wall Washing, Landscape lighting, Poster board lighting, Building lighting.

## FEATURES

- Rugged aluminum housing with UV resistant powder coat finish offers outstanding corrosion protection.
- Lumen output 1500-5400lm with efficacy to 120lm/W
- Three installation for option: 1/2" knuckle mount or trunnion or wall mount
- Wide Flood beam spread 7H x 7V
- Long life LEDs lasting up to 50,000hours
- IP66 rated and suitable for use in ambients from -40°C to 45°C (-40°F ~113°F).
- UL wet location listed



Size: 15W



Size: 30W



Size: 45W



## ELECTRICAL DATA

Number Of Drivers	Driver Current (mA)	Nominal Power (W)	INPUT VOLTAGE (V)	CURRENT (Amps)
1	250	15	120	0.13
		15	208	0.07
		15	240	0.06
		15	277	0.05
1	430	30	120	0.25
		30	208	0.14
		30	240	0.13
		30	277	0.11
1	1100	45	120	0.38
		45	208	0.22
		45	240	0.19
		45	277	0.16


## PERFORMANCE DATA

SYSTEM WATTS	VOLTAGE	DIST. TYPE	4000K(70CRI)		5000K(70CRI)	
			LUMENS	LPW	LUMENS	LPW
15W	120-277V	7Hx7V	1500lm	100 lm/W	1500lm	100 lm/W
30W	120-277V	7Hx7V	3000lm	100 lm/W	3000lm	100 lm/W
45W	120-277V	7Hx7V	5400lm	120 lm/W	5400lm	120 lm/W




# PHOTOMETRICS

15W



30W



45W

